



## JHWISFX614






**3/8 Drive, 7/16 , 6 Point  
Flexextension, Black Industrial  
Finish, (Non-Tension) 6"**



### PRODUCT DETAILS

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE™ lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 3 degree angle offset
- Flexextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 16 Ft. Lbs. /192 In. Lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

### PRODUCT ATTRIBUTES

| Product           |  | <b>A</b>        |  |  |  | <b>B</b>      | <b>C</b>       | <b>D</b>       | <b>E</b>     |  |
|-------------------|---|-----------------|---|---|---|---------------|----------------|----------------|--------------|---|
| <b>JHWISFX614</b> | 3/8 in  | 6.57in/166.9 mm | No  | 6   | 7/16 in   | 1.06"/26.9 mm | 0.90in/22.7 mm | 0.76in/19.3 mm | 0.3in/7.6 mm | 0.5 lb  |