



## JHWISFXM415






**3/8 Drive, 15 mm 6 Point  
Flexextension, Black Industrial  
Finish, (Non-Tension) 4"**



### PRODUCT DETAILS

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 3 degree angle offset
- Flexextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 16 Ft. Lbs. /192 In. Lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

### PRODUCT ATTRIBUTES

| Product     |  | A               |  |  |  | B             | C              | D              | E              |  |
|-------------|---|-----------------|---|---|---|---------------|----------------|----------------|----------------|---|
| JHWISFXM415 | 3/8 in  | 4.57in/116.1 mm | No  | 6   | 15 mm   | 1.06"/26.9 mm | 0.90in/22.7 mm | 0.88in/22.4 mm | 0.42in/10.7 mm | 0.4 lb  |