



**JHWISFXTM410**  
**3/8 Drive, 10 mm 6 Point**  
**Flextension, Black Industrial**  
**Finish, (Tension) 4"**



**PRODUCT DETAILS**

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 3 degree angle offset
- Flextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 16 Ft. Lbs. /192 In. Lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

**PRODUCT ATTRIBUTES**

| Product             |        | <b>A</b>        |     |   |       | <b>B</b>      | <b>C</b>       | <b>D</b>       | <b>E</b>      |         |
|---------------------|--------|-----------------|-----|---|-------|---------------|----------------|----------------|---------------|---------|
| <b>JHWISFXTM410</b> | 3/8 in | 4.57in/116.1 mm | Yes | 6 | 10 mm | 1.06"/26.9 mm | 0.90in/22.7 mm | 0.63in/16.0 mm | 0.28in/7.1 mm | 0.43 lb |