








**JHWISSX924**  
**1/2 Drive 3/4 6 Point Flextension,**  
**Black Industrial Finish, (Non-**  
**Tension) 9" Shank Length**



**PRODUCT DETAILS**

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 30 degree angle offset
- Flextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 160 ft-lbs. /1920 in-lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

**PRODUCT ATTRIBUTES**

| Product           |  | <b>A</b>        |  |  |  | <b>B</b>     | <b>C</b>       | <b>D</b>       | <b>E</b>       |  |
|-------------------|---|-----------------|---|---|---|--------------|----------------|----------------|----------------|---|
| <b>JHWISSX924</b> | 1/2 in  | 9.57in/243.1 mm | No  | 6   | 3/4 in  | 1.25/31.8 mm | 1.00in/25.4 mm | 1.12in/28.4 mm | 0.56in/14.2 mm | 0.79 lb   |