






**30604A - 30614A**  
**1/4 Drive Shallow Sockets, 12**  
**Point, Metric**



**PRODUCT DETAILS**

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Designed for maximum engagement on 12 point fasteners

**PRODUCT ATTRIBUTES**

Product			<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>		<b>F</b>	
<b>JHW30604A</b>	1/4 in	4 mm	1 in	15/32 in	1/4 in	1/4 in	19/32 in		1/4 in	0.03 lb
<b>JHW30605A</b>	1/4 in	5 mm	1 in	15/32 in	5/16 in	5/16 in	19/32 in		5/16 in	0.03 lb
<b>JHW30606A</b>	1/4 in	6 mm	1 in	15/32 in	11/32 in	5/16 in	19/32 in		5/16 in	0.03 lb
<b>JHW30607A</b>	1/4 in	7 mm	1 in	15/32 in	7/16 in	5/16 in	15/32 in		5/16 in	0.03 lb
<b>JHW30608A</b>	1/4 in	8 mm	1 in	15/32 in	15/32 in	3/8 in	1/2 in		3/8 in	0.03 lb
<b>JHW30609A</b>	1/4 in	9 mm	1 in	17/32 in	17/32 in	3/8 in	21/32 in		3/8 in	0.03 lb
<b>JHW30610A</b>	1/4 in	10 mm	1 in	19/32 in	19/32 in	1/2 in	7/8 in		1/2 in	0.04 lb
<b>JHW30611A</b>	1/4 in	11 mm	1 in	5/8 in	5/8 in	17/32 in	7/8 in		17/32 in	0.05 lb
<b>JHW30612A</b>	1/4 in	12 mm	1 in	11/16 in	11/16 in	1/2 in	7/8 in		1/2 in	0.05 lb
<b>JHW30613A</b>	1/4 in	13 mm	1 in	23/32 in	23/32 in	1/2 in	7/8 in		1/2 in	0.06 lb
<b>JHW30614A</b>	1/4 in	14 mm	1 in	3/4 in	3/4 in	1/2 in	7/8 in		1/2 in	0.08 lb