

31308 - 31332

3/8" Drive Deep Sockets 6 Point, SAE



PRODUCT DETAILS

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Designed for quick engagement on 6 point fasteners

PRODUCT ATTRIBUTES

| Product | | | A | В | C | D | E | \varnothing | F | lb |
|----------|--------|----------|----------|----------|----------|----------|------------|---------------|----------|---------|
| JHW31308 | 3/8 in | 1/4 in | 2-1/2 in | 11/16 in | 7/16 in | 11/32 in | 1-11/16 in | 7/32 in | 11/32 in | 0.11 lb |
| JHW31310 | 3/8 in | 5/16 in | 2-1/2 in | 11/16 in | 15/32 in | 3/8 in | 1-11/16 in | 5/16 in | 3/8 in | 0.11 lb |
| JHW31312 | 3/8 in | 3/8 in | 2-1/2 in | 11/16 in | 9/16 in | 3/8 in | 1-11/16 in | 3/8 in | 3/8 in | 0.12 lb |
| JHW31314 | 3/8 in | 7/16 in | 2-1/2 in | 11/16 in | 5/8 in | 11/32 in | 1-11/16 in | 7/16 in | 11/32 in | 0.2 lb |
| JHW31318 | 3/8 in | 9/16 in | 2-1/2 in | 25/32 in | 25/32 in | 17/32 in | 1-9/16 in | 17/32 in | 17/32 in | 0.25 lb |
| JHW31320 | 3/8 in | 5/8 in | 2-1/2 in | 7/8 in | 7/8 in | 19/32 in | 1-9/16 in | 19/32 in | 19/32 in | 0.3 lb |
| JHW31322 | 3/8 in | 11/16 in | 2-1/2 in | 15/16 in | 15/16 in | 1/2 in | 1-11/16 in | 21/32 in | 1/2 in | 0.34 lb |
| JHW31326 | 3/8 in | 13/16 in | 2-1/2 in | 1-1/8 in | 1-1/8 in | 9/16 in | 2-1/32 in | 25/32 in | 9/16 in | 0.5 lb |
| JHW31330 | 3/8 in | 15/16 in | 2-1/2 in | 1-1/4 in | 1-1/4 in | 21/32 in | 2-1/32 in | 27/32 in | 21/32 in | 0.44 lb |