



B-608 - B-632





**3/8 Drive Shallow Socket, 6 Point,
SAE**



PRODUCT DETAILS

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Designed for maximum engagement on 6 point fasteners

PRODUCT ATTRIBUTES

Product			A	B	C	D	E		F	
JHWB-608	3/8 in	1/4 in	1-1/32 in	11/16 in	13/32 in	7/32 in	9/16 in	1/2 in		0.05 lb
JHWB-610	3/8 in	5/16 in	1-1/32 in	11/16 in	7/16 in	1/4 in	9/16 in	1/2 in		0.05 lb
JHWB-611	3/8 in	11/32 in	1-1/32 in	11/16 in	1/2 in	9/32 in	9/16 in	1/2 in		0.05 lb
JHWB-612	3/8 in	3/8 in	1-1/32 in	11/16 in	9/16 in	9/32 in	9/16 in	1/2 in		0.05 lb
JHWB-614	3/8 in	7/16 in	1-1/32 in	11/16 in	5/8 in	5/16 in	9/16 in	1/2 in		0.05 lb
JHWB-616	3/8 in	1/2 in	1-1/32 in	23/32 in	23/32 in	11/32 in	9/16 in	— in		0.07 lb
JHWB-618	3/8 in	9/16 in	1-3/32 in	25/32 in	25/32 in	9/16 in	19/32 in	— in		0.07 lb
JHWB-620	3/8 in	5/8 in	1-1/8 in	27/32 in	27/32 in	19/32 in	5/8 in	— in		0.09 lb
JHWB-622	3/8 in	11/16 in	1-5/32 in	15/16 in	15/16 in	5/8 in	5/8 in	— in		0.12 lb
JHWB-624	3/8 in	3/4 in	1-3/16 in	1 in	1 in	21/32 in	11/16 in	— in		0.14 lb
JHWB-626	3/8 in	13/16 in	1-1/4 in	1-1/16 in	1-1/16 in	11/16 in	23/32 in	— in		0.16 lb
JHWB-628	3/8 in	7/8 in	1-9/32 in	1-5/32 in	1-5/32 in	3/4 in	25/32 in	— in		0.2 lb
JHWB-630	3/8 in	15/16 in	1-3/8 in	1-1/4 in	1-1/4 in	13/16 in	27/32 in	— in		0.26 lb
JHWB-632	3/8 in	1 in	1-13/32 in	1-5/16 in	1-5/16 in	27/32 in	7/8 in	— in		0.12 lb