







BM-605.5 - BM-624
3/8 Drive Shallow Socket, 6 Point,
Metric



PRODUCT DETAILS

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Designed for maximum engagement on 6 point fasteners

PRODUCT ATTRIBUTES

Product			A	B	C	D	E		F	
JHWBM-607	3/8 in	7-mm	7 in	1-1/32 in	11/16 in	13/32 in	7/32 in	9/16 in	7/32 in	0.05 lb
JHWBM-605.5	3/8 in	5.5-mm	1-1/32 in	11/16 in	13/32 in	7/32 in	9/16 in	3/16 in	17/32 in	0.05 lb
JHWBM-606	3/8 in	6-mm	6 in	1-1/32 in	11/16 in	13/32 in	7/32 in	9/16 in	7/32 in	0.05 lb
JHWBM-608	3/8 in	8-mm	8 in	1-1/32 in	11/16 in	15/32 in	1/4 in	9/16 in	9/32 in	0.05 lb
JHWBM-609	3/8 in	9-mm	9 in	1-1/32 in	11/16 in	1/2 in	9/32 in	9/16 in	11/32 in	0.05 lb
JHWBM-610	3/8 in	10-mm	10 in	1-1/32 in	11/16 in	9/16 in	9/32 in	9/16 in	11/32 in	0.05 lb
JHWBM-611	3/8 in	11-mm	11 in	1-1/32 in	11/16 in	5/8 in	9/32 in	9/16 in	11/32 in	0.06 lb
JHWBM-612	3/8 in	12-mm	12 in	1-1/32 in	11/16 in	21/32 in	11/32 in	9/16 in	11/32 in	0.06 lb
JHWBM-613	3/8 in	13-mm	13 in	1-1/32 in	23/32 in	23/32 in	11/32 in	9/16 in	3/8 in	0.06 lb
JHWBM-614	3/8 in	14-mm	14 in	1-1/32 in	25/32 in	25/32 in	7/16 in	17/32 in	17/32 in	0.07 lb
JHWBM-615	3/8 in	15-mm	15 in	1-3/32 in	13/16 in	13/16 in	19/32 in	19/32 in	9/16 in	0.08 lb
JHWBM-616	3/8 in	16-mm	16 in	1-1/8 in	27/32 in	27/32 in	19/32 in	5/8 in	19/32 in	0.09 lb
JHWBM-617	3/8 in	17-mm	17 in	1-5/32 in	29/32 in	29/32 in	5/8 in	5/8 in	5/8 in	0.11 lb
JHWBM-618	3/8 in	18-mm	18 in	1-5/32 in	31/32 in	31/32 in	5/8 in	21/32 in	11/16 in	0.13 lb
JHWBM-619	3/8 in	19-mm	19 in	1-3/16 in	1 in	1 in	21/32 in	11/16 in	23/32 in	0.14 lb
JHWBM-620	3/8 in	20-mm	1-7/32 in	1-1/32 in	1-1/32 in	11/16 in	23/32 in	3/4 in		0.14 lb
JHWBM-621	3/8 in	21-mm	1-1/4 in	1-1/8 in	1-1/8 in	23/32 in	23/32 in	3/16 in		0.22 lb
JHWBM-622	3/8 in	22-mm	1-9/32 in	1-5/32 in	1-5/32 in	3/4 in	3/4 in	3/16 in		0.18 lb
JHWBM-623	3/8 in	23-mm	1-5/16 in	1-3/16 in	1-3/16 in	3/4 in	25/32 in	7/8 in		0.22 lb
JHWBM-624	3/8 in	24-mm	1-3/8 in	1-1/4 in	1-1/4 in	13/16 in	27/32 in	7/8 in		0.27 lb