







BU-1212 - BU-1224
3/8 Drive Universal Socket, 12
Point, SAE



PRODUCT DETAILS

- 5 point Penta-Socket services 5 point nuts found on tamper-resistant Buffalo covers used by gas, electric, and some water companies to protect shutoff gates
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Metal tool box made for years of rugged use
- Display can be turned 18 degrees to allow left hand usage
- Battery cover designed to be aviation FOD proof
- Holds “peak” torque reading for 1 seconds
- Constructed of special Capron® material for long life and durability
- Resistant to the majority of chemicals used in industrial environments
- Wrench can be hung on tool board
- Bar graph displays orientation of torque application (left or right hand)
- Uses standard 9 volt alkaline battery
- N.I.S.T. traceable certificate of calibration included
- Meets or exceeds ASME B17.3 – 21

PRODUCT ATTRIBUTES

Product			A	B	C	D	E		F	
JHWBU-1212	3/8 in	3/8 in	1-25/32 in	3/4 in	1/2 in	1/4 in	1/2 in	5/16 in	15/64 in	0.26 lb
JHWBU-1214	3/8 in	7/16 in	1-25/32 in	3/4 in	5/8 in	1/4 in	1/2 in	11/32 in	15/64 in	0.12 lb
JHWBU-1216	3/8 in	1/2 in	1-25/32 in	3/4 in	11/16 in	5/16 in	9/16 in	11/32 in	9/32 in	0.12 lb
JHWBU-1218	3/8 in	9/16 in	1-25/32 in	3/4 in	3/4 in	11/32 in	5/8 in	11/32 in	17/32 in	0.13 lb
JHWBU-1220	3/8 in	5/8 in	1-25/32 in	3/4 in	7/8 in	13/32 in	11/16 in	11/32 in	17/32 in	0.14 lb
JHWBU-1222	3/8 in	11/16 in	2 in	3/4 in	15/16 in	7/16 in	23/32 in	11/32 in	17/32 in	0.15 lb
JHWBU-1224	3/8 in	3/4 in	2-1/8 in	3/4 in	1 in	17/32 in	13/16 in	11/32 in	5/8 in	0.15 lb