







TS38375 - TS38750
3/8 Drive Turbosocket
Salvage/Damaged Fastener
Sockets, Metric & SAE



PRODUCT DETAILS

- Quickly and easily remove damaged or rounded nuts and bolts
- Place socket on fastener and turn with ratchet, breaker bar or T-handle
- Grip on fastener tightens as more torque is applied
- No hammering is required to install socket over fastener
- Use on all types of standard nuts and bolts as well as studs, pipe nipples, and corroded auto and marine fasteners
- May be used for "best fit" on metric and fractional fasteners

PRODUCT ATTRIBUTES

Product			A	B	C	D	E		F	
JHWTS38375	3/8 in	3/8 in	1-1/4 in	11/16 in	19/32 in	13/32 in	3/4 in	3/8 in	11/16 in	0.06 lb
JHWTS38394	3/8 in	10-mm	1-1/4 in	11/16 in	5/8 in	13/32 in	3/4 in	13/32 in	11/16 in	0.06 lb
JHWTS38437	3/8 in	7/16 in	1-1/4 in	11/16 in	21/32 in	1/2 in	3/4 in	7/16 in	11/16 in	0.07 lb
JHWTS38472	3/8 in	12-mm	1-1/4 in	23/32 in	23/32 in	1/2 in	3/4 in	15/32 in		0.07 lb
JHWTS38500	3/8 in	1/2 in	1-1/4 in	3/4 in	3/4 in	1/2 in	3/4 in	1/2 in		0.07 lb
JHWTS38512	3/8 in	13-mm	1-1/4 in	3/4 in	3/4 in	1/2 in	3/4 in	17/32 in		0.07 lb
JHWTS38551	3/8 in	14-mm	1-1/4 in	13/16 in	13/16 in	1/2 in	23/32 in	9/16 in		0.07 lb
JHWTS38562	3/8 in	9/16 in	1-1/4 in	13/16 in	13/16 in	1/2 in	23/32 in	9/16 in		0.07 lb
JHWTS38591	3/8 in	15-mm	1-1/4 in	27/32 in	27/32 in	1/2 in	19/32 in	19/32 in		0.1 lb
JHWTS38625	3/8 in	5/8 in	1-1/4 in	29/32 in	29/32 in	1/2 in	19/32 in	5/8 in		0.1 lb
JHWTS38669	3/8 in	17-mm	1-13/32 in	31/32 in	31/32 in	21/32 in	29/32 in	23/32 in		0.11 lb
JHWTS38687	3/8 in	11/16 in	1-13/32 in	31/32 in	31/32 in	21/32 in	29/32 in	23/32 in		0.1 lb
JHWTS38750	3/8 in	3/4 in	1-13/32 in	1-1/16 in	1-1/16 in	21/32 in	29/32 in	3/4 in		0.17 lb