








ISFX618 - ISFX620
3/8 Drive Flextension, Non-Tension, 6 Point, 6.57 Shank Length, SAE



PRODUCT DETAILS

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE™ lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 3 degree angle offset
- Flextorques are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 16 Ft. Lbs. /192 In. Lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

PRODUCT ATTRIBUTES

Product		A				B	C	D	E	
JHWISFX618	3/8 in	6.57in/166.9 mm	No	6	9/16 in	1.06"/26.9 mm	0.90in/22.7 mm	0.82in/20.8 mm	0.44in/11.2 mm	0.5 lb
JHWISFX620	3/8 in	6.57in/166.9 mm	No	6	5/8 in	1.06"/26.9 mm	0.90in/22.7 mm	0.90in/22.7 mm	0.44in/11.2 mm	0.5 lb