



ISFXM410 - ISFXM416
3/8 Drive Flextension, Non-Tension, 6 Point, 4.57" Shank Length, Metric



PRODUCT DETAILS

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 3 degree angle offset
- Flextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 16 Ft. Lbs. /192 In. Lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

PRODUCT ATTRIBUTES

Product		A				B	C	D	E	
JHWISFXM410	3/8 in	4.57in/116.1 mm	No	6	10 mm	1.06"/26.9 mm	0.90in/22.7 mm	0.63in/16.0 mm	0.28in/7.1 mm	0.4 lb
JHWISFXM412	3/8 in	4.57in/116.1 mm	No	6	12 mm	1.06"/26.9 mm	0.90in/22.7 mm	0.76in/19.3 mm	0.34in/8.6 mm	0.4 lb
JHWISFXM415	3/8 in	4.57in/116.1 mm	No	6	15 mm	1.06"/26.9 mm	0.90in/22.7 mm	0.88in/22.4 mm	0.42in/10.7 mm	0.4 lb
JHWISFXM416	3/8 in	4.57in/116.1 mm	No	6	16 mm	1.06"/26.9 mm	0.90in/22.7 mm	0.90in/22.7 mm	0.45in/11.4 mm	0.39 lb