## ISFXM410 - ISFXM416

# 3/8 Drive Flextension, Non-Tension, 6 Point, 4.57" Shank Length, Metric

## PRODUCT DETAILS

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 3 degree angle offset
- Flextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 16 Ft. Lbs. /192 In. Lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

## PRODUCT ATTRIBUTES

| Product | | A | | # | | B | C | D | E | lb |
|---|---|---|---|---|---|---|---|---|---|---|
| JHWISFXM410 | 3/8 in | 4.57in/116.1 mm | No | 6 | 10 mm | 1.06"/26.9 mm | 0.90in/22.7 mm | 0.63in/16.0 mm | 0.28in/7.1 mm | 0.4 lb |
| JHWISFXM412 | 3/8 in | 4.57in/116.1 mm | No | 6 | 12 mm | 1.06"/26.9 mm | 0.90in/22.7 mm | 0.76in/19.3 mm | 0.34in/8.6 mm | 0.4 lb |
| JHWISFXM415 | 3/8 in | 4.57in/116.1 mm | No | 6 | 15 mm | 1.06"/26.9 mm | 0.90in/22.7 mm | 0.88in/22.4 mm | 0.42in/10.7 mm | 0.4 lb |
| JHWISFXM416 | 3/8 in | 4.57in/116.1 mm | No | 6 | 16 mm | 1.06"/26.9 mm | 0.90in/22.7 mm | 0.90in/22.7 mm | 0.45in/11.4 mm | 0.39 lb |