








ISFXT612 - ISFXT620
3/8 Drive Flexextension, Tension, 6
Point, 6.57" Shank Length, SAE



PRODUCT DETAILS

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 3 degree angle offset
- Flexextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 16 Ft. Lbs. /192 In. Lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

PRODUCT ATTRIBUTES

Product		A				B	C	D	E	
JHWISFXT612	3/8 in	6.57in/166.9 mm	Yes	6	3/8 in	1.06"/26.9 mm	0.90in/22.7 mm	0.63in/16.0 mm	0.28in/7.1 mm	0.55 lb
JHWISFXT614	3/8 in	6.57in/166.9 mm	Yes	6	7/16 in	1.06"/26.9 mm	0.90in/22.7 mm	0.76in/19.3 mm	0.3in/7.6 mm	0.55 lb
JHWISFXT616	3/8 in	6.57in/166.9 mm	Yes	6	1/2 in	1.06"/26.9 mm	0.90in/22.7 mm	0.76in/19.3 mm	0.34in/8.6 mm	0.53 lb
JHWISFXT618	3/8 in	6.57in/166.9 mm	Yes	6	9/16 in	1.06"/26.9 mm	0.90in/22.7 mm	0.82in/20.8 mm	0.44in/11.2 mm	0.54 lb
JHWISFXT620	3/8 in	6.57in/166.9 mm	Yes	6	5/8 in	1.06"/26.9 mm	0.90in/22.7 mm	0.90in/22.7 mm	0.44in/11.2 mm	0.55 lb