



ISFXTM410 - ISFXTM416
3/8 Drive Flexextension, Tension, 6
Point, 4.57 Shank Length, Metric



PRODUCT DETAILS

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 3 degree angle offset
- Flexextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 16 Ft. Lbs. /192 In. Lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

PRODUCT ATTRIBUTES

Product		A				B	C	D	E	
JHWISFXTM410	3/8 in	4.57in/116.1 mm	Yes	6	10 mm	1.06"/26.9 mm	0.90in/22.7 mm	0.63in/16.0 mm	0.28in/7.1 mm	0.43 lb
JHWISFXTM412	3/8 in	4.57in/116.1 mm	Yes	6	12 mm	1.06"/26.9 mm	0.90in/22.7 mm	0.76in/19.3 mm	0.34in/8.6 mm	0.45 lb
JHWISFXTM413	3/8 in	4.57in/116.1 mm	Yes	6	13 mm	1.06"/26.9 mm	0.90in/22.7 mm	0.76in/19.3 mm	0.34in/8.6 mm	0.55 lb
JHWISFXTM415	3/8 in	4.57in/116.1 mm	Yes	6	15 mm	1.06"/26.9 mm	0.90in/22.7 mm	0.88in/22.4 mm	0.42in/10.7 mm	0.45 lb
JHWISFXTM416	3/8 in	4.57in/116.1 mm	Yes	6	16 mm	1.06"/26.9 mm	0.90in/22.7 mm	0.90in/22.7 mm	0.45in/11.4 mm	0.52 lb