



12-610 - 12-632





3/8" Drive Deep Impact Sockets, 6 Point, SAE, Black Industrial Finish



PRODUCT DETAILS

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability

PRODUCT ATTRIBUTES

Product			A	B	C	D	E		F	
JHW12-610	3/8 in	5/16 in	2-1/8 in	11/16 in	1/2 in	1/4 in	1-21/32 in	9/32 in	1/4 in	0.1 lb
JHW12-612	3/8 in	3/8 in	2-1/8 in	11/16 in	5/8 in	9/32 in	1-5/8 in	11/32 in	9/32 in	0.11 lb
JHW12-614	3/8 in	7/16 in	2-1/8 in	11/16 in	21/32 in	11/32 in	1-5/8 in	11/32 in	11/32 in	0.13 lb
JHW12-616	3/8 in	1/2 in	2-1/8 in	3/4 in	3/4 in	3/8 in	1-15/32 in	7/16 in	3/8 in	0.17 lb
JHW12-618	3/8 in	9/16 in	2-3/8 in	13/16 in	13/16 in	7/16 in	1-1/2 in	17/32 in	7/16 in	0.2 lb
JHW12-620	3/8 in	5/8 in	2-3/8 in	29/32 in	29/32 in	15/32 in	11/2 in	5/8 in	15/32 in	0.24 lb
JHW12-622	3/8 in	11/16 in	2-5/8 in	31/32 in	31/32 in	1/2 in	1-19/32 in	21/32 in	1/2 in	0.3 lb
JHW12-624	3/8 in	3/4 in	2-5/8 in	1-1/16 in	1-1/16 in	9/16 in	1-19/32 in	23/32 in	9/16 in	0.37 lb
JHW12-626	3/8 in	13/16 in	2-3/4 in	1-1/8 in	1-1/8 in	9/16 in	1-25/32 in	25/32 in	9/16 in	0.37 lb
JHW12-628	3/8 in	7/8 in	2-3/4 in	1-3/16 in	1-3/16 in	19/32 in	1-7/8 in	27/32 in	19/32 in	0.47 lb
JHW12-630	3/8 in	15/16 in	2-3/4 in	1-9/32 in	1-9/32 in	19/32 in	1-15/16 in	29/32 in	19/32 in	0.55 lb
JHW12-632	3/8 in	1 in	2-3/4 in	1-11/32 in	1-11/32 in	5/8 in	2 in	1 in	5/8 in	0.45 lb