



2-608 - 2-632

**3/8" Drive Shallow Impact
Sockets, 6 Point, SAE, Black
Industrial Finish**



PRODUCT DETAILS

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability

PRODUCT ATTRIBUTES

Product			A	B	C	D	E		F	
JHW2-608	3/8 in	1/4 in	1-1/32 in	11/16 in	1/2 in	7/32 in	9/16 in	7/32 in	7/32 in	0.06 lb
JHW2-610	3/8 in	5/16 in	1-1/32 in	11/16 in	1/2 in	1/4 in	9/16 in	9/32 in	1/4 in	0.05 lb
JHW2-612	3/8 in	3/8 in	1-1/32 in	11/16 in	5/8 in	9/32 in	9/16 in	11/32 in	9/32 in	0.04 lb
JHW2-614	3/8 in	7/16 in	1-1/16 in	11/16 in	21/32 in	9/32 in	19/32 in	11/32 in	9/32 in	0.06 lb
JHW2-616	3/8 in	1/2 in	1-1/16 in	3/4 in	3/4 in	5/16 in	19/32 in	3/8 in	5/16 in	0.09 lb
JHW2-618	3/8 in	9/16 in	1-3/32 in	13/16 in	13/16 in	9/16 in	19/32 in	17/32 in	9/16 in	0.12 lb
JHW2-620	3/8 in	5/8 in	1-1/8 in	29/32 in	29/32 in	19/32 in	5/8 in	5/8 in	19/32 in	0.12 lb
JHW2-622	3/8 in	11/16 in	1-5/32 in	31/32 in	31/32 in	19/32 in	5/8 in	21/32 in	19/32 in	0.13 lb
JHW2-624	3/8 in	3/4 in	1-3/16 in	1-1/16 in	1-1/16 in	21/32 in	11/16 in	23/32 in	21/32 in	0.17 lb
JHW2-626	3/8 in	13/16 in	1-1/4 in	1-1/8 in	1-1/8 in	11/16 in	23/32 in	25/32 in	11/16 in	0.2 lb
JHW2-628	3/8 in	7/8 in	1-9/32 in	1-3/16 in	1-3/16 in	3/4 in	3/4 in	27/32 in	3/4 in	0.3 lb
JHW2-630	3/8 in	15/16 in	1-5/16 in	1-9/32 in	1-9/32 in	25/32 in	13/16 in	29/32 in	25/32 in	0.27 lb
JHW2-632	3/8 in	1 in	1-5/16 in	1-11/32 in	1-11/32 in	25/32 in	25/32 in	31/32 in	25/32 in	0.3 lb