



2M-607 - 2M-619
3/8" Drive Shallow Impact
Sockets, 6 Point, Metric, Black
Industrial Finish



PRODUCT DETAILS

- SUPERTORQUE™ lobular openings for greater turning power without deforming the fastener
- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability

PRODUCT ATTRIBUTES

Product			A	B	C	D	E		F	
JHW2M-607	3/8 in	7 mm	1-1/32 in	11/16 in	7/16 in	7/32 in	9/16 in	1/4 in	7/32 in	0.06 lb
JHW2M-608	3/8 in	8 mm	1-1/32 in	11/16 in	1/2 in	1/4 in	9/16 in	9/32 in	1/4 in	0.05 lb
JHW2M-609	3/8 in	9 mm	1-1/32 in	11/16 in	9/16 in	9/32 in	9/16 in	11/32 in	9/32 in	0.06 lb
JHW2M-610	3/8 in	10 mm	1-1/32 in	11/16 in	5/8 in	9/32 in	9/16 in	11/32 in	9/32 in	0.06 lb
JHW2M-611	3/8 in	11 mm	1-1/32 in	11/16 in	21/32 in	9/32 in	19/32 in	11/32 in	9/32 in	0.07 lb
JHW2M-612	3/8 in	12 mm	1-1/16 in	23/32 in	23/32 in	9/32 in	9/16 in	11/32 in	9/32 in	0.08 lb
JHW2M-613	3/8 in	13 mm	1-1/16 in	25/32 in	25/32 in	9/32 in	19/32 in	3/8 in	9/32 in	0.1 lb
JHW2M-614	3/8 in	14 mm	1-3/32 in	13/16 in	13/16 in	9/16 in	19/32 in	1/2 in	9/16 in	0.08 lb
JHW2M-615	3/8 in	15 mm	1-3/32 in	27/32 in	27/32 in	9/16 in	19/32 in	9/16 in	9/16 in	0.09 lb
JHW2M-616	3/8 in	16 mm	1-1/8 in	29/32 in	29/32 in	19/32 in	5/8 in	19/32 in	19/32 in	0.13 lb
JHW2M-617	3/8 in	17 mm	1-5/32 in	31/32 in	31/32 in	19/32 in	5/8 in	5/8 in	19/32 in	0.14 lb
JHW2M-618	3/8 in	18 mm	1-5/32 in	1 in	1 in	5/8 in	21/32 in	11/16 in	5/8 in	0.14 lb
JHW2M-619	3/8 in	19 mm	1-3/16 in	1-1/16 in	1-1/16 in	21/32 in	11/16 in	23/32 in	21/32 in	0.17 lb