



**36410 - 36432**  
**3/8" Drive Deep Impact Sockets,**  
**12 Point, SAE**







---

## PRODUCT DETAILS

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Designed for maximum engagement on 6 or 12 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove

PRODUCT ATTRIBUTES

Product			<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>		<b>F</b>	
<b>JHW36410</b>	3/8 in	5/16 in	2-1/2 in	3/4 in	1/2 in	1/2 in		3/8 in	1-1/4 in	0.16 lb
<b>JHW36412</b>	3/8 in	3/8 in	2-1/2 in	3/4 in	1/2 in	3/4 in		1/2 in	1-1/4 in	0.15 lb
<b>JHW36414</b>	3/8 in	7/16 in	2-1/2 in	3/4 in	5/8 in	3/4 in		1/2 in	1-1/4 in	0.18 lb
<b>JHW36416</b>	3/8 in	1/2 in	2-1/2 in	3/4 in	3/4 in	1 in		1/2 in		0.17 lb
<b>JHW36418</b>	3/8 in	9/16 in	2-1/2 in	3/4 in	3/4 in	1 in		1/2 in		0.18 lb
<b>JHW36420</b>	3/8 in	5/8 in	2-1/2 in	1 in	1 in	1 in		1/2 in		0.3 lb
<b>JHW36422</b>	3/8 in	11/16 in	2-1/2 in	1 in	1 in	1 in		1/2 in		0.27 lb
<b>JHW36424</b>	3/8 in	3/4 in	2-1/2 in	1 in	1 in	1 in		3/4 in		0.32 lb
<b>JHW36426</b>	3/8 in	13/16 in	2-1/2 in	1 in	1 in	1 in		3/4 in		0.37 lb
<b>JHW36428</b>	3/8 in	7/8 in	2-1/2 in	1-1/8 in	1-1/8 in	1 in		3/4 in		0.44 lb
<b>JHW36430</b>	3/8 in	15/16 in	2-1/2 in	1-1/4 in	1-1/4 in	1 in		5/8 in		0.5 lb
<b>JHW36432</b>	3/8 in	1 in	2-1/2 in	1-3/8 in	1-3/8 in	1 in		1 in		0.57 lb