







TS50100 - TS51827
1/2" Drive TURBOSOCKET®
Salvage/Damaged Fastener
Sockets



PRODUCT DETAILS

- Quickly and easily remove damaged or rounded nuts and bolts
- Place socket on fastener and turn with ratchet, breaker bar or T-handle
- Grip on fastener tightens as more torque is applied
- No hammering is required to install socket over fastener
- Use on all types of standard nuts and bolts as well as studs, pipe nipples, and corroded auto and marine fasteners
- May be used for "best fit" on metric and fractional fasteners
- May be used with air or electric impact wrench for extra speed and turning power

PRODUCT ATTRIBUTES

Product			A	B	C	D	E		F	
JHWTS50100	1/2 in	1 in	1-21/32 in	1-11/32 in	1-11/32 in	23/32 in	1 in	1 in		0.3 lb
JHWTS50750	1/2 in	3/4 in	1-21/32 in	1-1/16 in	1-1/16 in	23/32 in	1 in	3/4 in		0.2 lb
JHWTS50812	1/2 in	13/16 in	1-21/32 in	1-1/8 in	1-1/8 in	23/32 in	1 in	13/16 in		0.21 lb
JHWTS50875	1/2 in	7/8 in	1-21/32 in	1-3/16 in	1-3/16 in	23/32 in	1 in	7/8 in		0.2 lb
JHWTS50937	1/2 in	15/16 in	1-21/32 in	1-5/16 in	1-5/16 in	23/32 in	1 in	15/16 in		0.29 lb
JHWTS51551	1/2 in	14-mm	1-21/32 in	29/32 in	27/32 in	1/2 in	1 in	9/16 in	29/32 in	0.18 lb
JHWTS51591	1/2 in	15-mm	1-21/32 in	29/32 in	29/32 in	1/2 in	1 in	19/32 in		0.19 lb
JHWTS51625	1/2 in	16-mm	1-21/32 in	31/32 in	31/32 in	1/2 in	23/32 in	5/8 in		0.19 lb
JHWTS51669	1/2 in	17-mm	1-21/32 in	1 in	1 in	21/32 in	23/32 in	11/16 in		0.21 lb
JHWTS51709	1/2 in	18-mm	1-21/32 in	1-1/32 in	1-1/32 in	21/32 in	23/32 in	23/32 in		0.21 lb
JHWTS51750	1/2 in	19-mm	1-21/32 in	1-1/16 in	1-1/16 in	23/32 in	1 in	3/4 in		0.21 lb
JHWTS51827	1/2 in	21-mm	1-21/32 in	1-3/16 in	1-3/16 in	21/32 in	1 in	27/32 in		0.22 lb