








**ISSX312 - ISSX324**  
**1/2" Drive Socket Flexextensions,**  
**Tension, 3.02" Shank Length, SAE**



**PRODUCT DETAILS**

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 30 degree angle offset
- Flexextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 16 Ft. Lbs. /192 In. Lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

**PRODUCT ATTRIBUTES**

Product		<b>A</b>				<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	
<b>JHWISSX312</b>	1/2 in	3.02in/76.7 mm	No	6	3/8 in	1.06/26.9 mm	0.90in/22.7 mm	0.63in/16.0 mm	0.28in/7.1 mm	0.4 lb
<b>JHWISSX314</b>	1/2 in	3.02in/76.7 mm	No	6	7/16 in	1.06/26.9 mm	0.90in/22.7 mm	0.76in/19.3 mm	0.3in/7.6 mm	0.4 lb
<b>JHWISSX316</b>	1/2 in	3.02in/76.7 mm	No	6	1/2 in	1.06/26.9 mm	0.90in/22.7 mm	0.76in/19.3 mm	0.34in/8.6 mm	0.4 lb
<b>JHWISSX320</b>	1/2 in	3.02in/76.7 mm	No	6	5/8 in	1.06/26.9 mm	0.90in/22.7 mm	0.90in/22.7 mm	0.44in/11.2 mm	0.4 lb
<b>JHWISSX324</b>	1/2 in	3.02in/76.7 mm	No	6	3/4 in	1.25/31.8 mm	1.00in/25.4 mm	1.12in/28.4 mm	0.56in/14.2 mm	0.59 lb