








ISSX412 - ISSX430
1/2" Drive Socket Flextensions,
Tension, 4.09" Shank Length, SAE



PRODUCT DETAILS

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 30 degree angle offset
- Flextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 16 Ft. Lbs. /192 In. Lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

PRODUCT ATTRIBUTES

Product		A				B	C	D	E	
JHWISSX412	1/2 in	4.09in/103.9 mm	No	6	3/8 in	1.06/26.9 mm	0.90in/22.7 mm	0.63in/16.0 mm	0.28in/7.1 mm	0.4 lb
JHWISSX414	1/2 in	4.09in/103.9 mm	No	6	7/16 in	1.06/26.9 mm	0.90in/22.7 mm	0.76in/19.3 mm	0.3in/7.6 mm	0.4 lb
JHWISSX416	1/2 in	4.09in/103.9 mm	No	6	1/2 in	1.06/26.9 mm	0.90in/22.7 mm	0.76in/19.3 mm	0.34in/8.6 mm	0.4 lb
JHWISSX418	1/2 in	4.09in/103.9 mm	No	6	9/16 in	1.06/26.9 mm	0.90in/22.7 mm	0.82in/20.8 mm	0.44in/11.2 mm	0.44 lb
JHWISSX420	1/2 in	4.09in/103.9 mm	No	6	5/8 in	1.06/26.9 mm	0.90in/22.7 mm	0.90in/22.7 mm	0.44in/11.2 mm	0.4 lb
JHWISSX424	1/2 in	4.09in/103.9 mm	No	6	3/4 in	1.25/31.8 mm	1.00in/25.4 mm	1.12in/28.4 mm	0.56in/14.2 mm	0.4 lb
JHWISSX430	1/2 in	4.09in/103.9 mm	No	6	15/16 in	1.31/33.3 mm	1.00in/25.4 mm	1.30in/33.0 mm	0.62in/15.7 mm	0.4 lb