



**ISSX612 - ISSX624**  
**1/2" Drive Socket Flexextensions,**  
**Tension, 6.57" Shank Length, SAE**



**PRODUCT DETAILS**

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 30 degree angle offset
- Flexextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 16 Ft. Lbs. /192 In. Lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

**PRODUCT ATTRIBUTES**

Product		<b>A</b>				<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	
<b>JHWISSX612</b>	1/2 in	6.57in/166.9 mm	No	6	3/8 in	1.06/26.9 mm	0.90in/22.7 mm	0.63in/16.0 mm	0.28in/7.1 mm	0.5 lb
<b>JHWISSX614</b>	1/2 in	6.57in/166.9 mm	No	6	7/16 in	1.06/26.9 mm	0.90in/22.7 mm	0.76in/19.3 mm	0.3in/7.6 mm	0.5 lb
<b>JHWISSX618</b>	1/2 in	6.57in/166.9 mm	No	6	9/16 in	1.06/26.9 mm	0.90in/22.7 mm	0.82in/20.8 mm	0.44in/11.2 mm	0.52 lb
<b>JHWISSX620</b>	1/2 in	6.57in/166.9 mm	No	6	5/8 in	1.06/26.9 mm	0.90in/22.7 mm	0.90in/22.7 mm	0.44in/11.2 mm	0.55 lb
<b>JHWISSX624</b>	1/2 in	6.57in/166.9 mm	No	6	3/4 in	1.25/31.8 mm	1.00in/25.4 mm	1.12in/28.4 mm	0.56in/14.2 mm	0.63 lb
<b>JHWISSX630</b>	1/2 in	6.57in/166.9 mm	No	6	15/16 in	1.31/33.3 mm	1.00in/25.4 mm	1.30in/33.0 mm	0.62in/15.7 mm	0.62 lb