








ISSX912 - ISSX930
1/2" Drive Socket Flexextensions,
Tension, 9.57" Shank Length, SAE



PRODUCT DETAILS

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 30 degree angle offset
- Flexextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 160 ft-lbs. /1920 in-lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

PRODUCT ATTRIBUTES

| Product |  | A |  |  |  | B | C | D | E |  |
|-------------------|---|-----------------|---|---|---|--------------|----------------|----------------|----------------|---|
| JHWISSX912 | 1/2 in | 9.57in/243.1 mm | No | 6 | 3/8 in | 1.06/26.9 mm | 0.90in/22.7 mm | 0.63in/16.0 mm | 0.28in/7.1 mm | 0.7 lb |
| JHWISSX914 | 1/2 in | 9.57in/243.1 mm | No | 6 | 7/16 in | 1.06/26.9 mm | 0.90in/22.7 mm | 0.76in/19.3 mm | 0.3in/7.6 mm | 0.7 lb |
| JHWISSX916 | 1/2 in | 9.57in/243.1 mm | No | 6 | 1/2 in | 1.06/26.9 mm | 0.90in/22.7 mm | 0.76in/19.3 mm | 0.34in/8.6 mm | 0.7 lb |
| JHWISSX918 | 1/2 in | 9.57in/243.1 mm | No | 6 | 9/16 in | 1.06/26.9 mm | 0.90in/22.7 mm | 0.82in/20.8 mm | 0.44in/11.2 mm | 0.69 lb |
| JHWISSX920 | 1/2 in | 9.57in/243.1 mm | No | 6 | 5/8 in | 1.06/26.9 mm | 0.90in/22.7 mm | 0.90in/22.7 mm | 0.44in/11.2 mm | 0.73 lb |
| JHWISSX924 | 1/2 in | 9.57in/243.1 mm | No | 6 | 3/4 in | 1.25/31.8 mm | 1.00in/25.4 mm | 1.12in/28.4 mm | 0.56in/14.2 mm | 0.79 lb |
| JHWISSX930 | 1/2 in | 9.57in/243.1 mm | No | 6 | 15/16 in | 1.31/33.3 mm | 1.00in/25.4 mm | 1.30in/33.0 mm | 0.62in/15.7 mm | 0.8 lb |