



**ISSXM410 - ISSXM413**  
**1/2" Drive Socket Flexextensions,**  
**Tension, 4.09" Shank Length,**  
**10mm - 13 mm, Metric**



**PRODUCT DETAILS**

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 30 degree angle offset
- Flexextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 16 Ft. Lbs. /192 In. Lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

**PRODUCT ATTRIBUTES**

Product		A				B	C	D	E	
<b>JHWISSXM410</b>	1/2 in	4.09in/103.9 mm	No	6	10 mm	1.06/26.9 mm	0.90in/22.7 mm	0.63in/16.0 mm	0.28in/7.1 mm	0.4 lb
<b>JHWISSXM412</b>	1/2 in	4.09in/103.9 mm	No	6	12 mm	1.06/26.9 mm	0.90in/22.7 mm	0.76in/19.3 mm	0.34in/8.6 mm	0.4 lb
<b>JHWISSXM413</b>	1/2 in	4.09in/103.9 mm	No	6	13 mm	1.06/26.9 mm	0.90in/22.7 mm	0.76in/19.3 mm	0.34in/8.6 mm	0.4 lb