



**ISSXM415 - ISSXM418**  
**1/2" Drive Socket Flexextensions,**  
**Tension, 4.09" Shank Length, 15**  
**mm - 18 mm, Metric**



**PRODUCT DETAILS**

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 30 degree angle offset
- Flexextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 16 Ft. Lbs. /192 In. Lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

**PRODUCT ATTRIBUTES**

Product		A		#		B	C	D	E	lb
<b>JHWISSXM415</b>	1/2 in	4.09in/103.9 mm	No	6	15 mm	1.06/26.9 mm	0.90in/22.7 mm	0.88in/22.4 mm	0.42in/10.7 mm	0.4 lb
<b>JHWISSXM416</b>	1/2 in	4.09in/103.9 mm	No	6	16 mm	1.06/26.9 mm	0.90in/22.7 mm	0.90in/22.7 mm	0.45in/11.4 mm	0.44 lb
<b>JHWISSXM418</b>	1/2 in	4.09in/103.9 mm	No	6	18 mm	1.06/26.9 mm	1.00in/25.4 mm	1.00in/25.4 mm	0.45in/11.4 mm	0.47 lb