



ISSXM610 - ISSXM613
1/2" Drive Socket Flexextensions,
Tension, 6.57" Shank Length, 10
mm - 13 mm, Metric



PRODUCT DETAILS

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 30 degree angle offset
- Flexextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 16 Ft. Lbs. /192 In. Lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

PRODUCT ATTRIBUTES

Product		A				B	C	D	E	
JHWISSXM610	1/2 in	6.57in/166.9 mm	No	6	10 mm	1.06/26.9 mm	0.90in/22.7 mm	0.63in/16.0 mm	0.28in/7.1 mm	0.55 lb
JHWISSXM612	1/2 in	6.57in/166.9 mm	No	6	12 mm	1.06/26.9 mm	0.90in/22.7 mm	0.76in/19.3 mm	0.34in/8.6 mm	0.55 lb
JHWISSXM613	1/2 in	6.57in/166.9 mm	No	6	13 mm	1.06/26.9 mm	0.90in/22.7 mm	0.76in/19.3 mm	0.34in/8.6 mm	0.55 lb