



**ISSXT1218 - ISSXT1230**  
**1/2" Drive Socket Flexextensions,**  
**non-Tension, 12.57" Shank Length,**  
**SAE**



**PRODUCT DETAILS**

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 30 degree angle offset
- Flexextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 16 Ft. Lbs. /192 In. Lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

**PRODUCT ATTRIBUTES**

Product		<b>A</b>				<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	
<b>JHWISSXT1218</b>	1/2 in	12.57in/319.3 mm	Yes	6	9/16 in	1.06/26.9 mm	0.90in/22.7 mm	0.82in/20.8 mm	0.44in/11.2 mm	0.92 lb
<b>JHWISSXT1230</b>	1/2 in	12.57in/319.3 mm	Yes	6	15/16 in	1.31/33.3 mm	1.00in/25.4 mm	1.30in/33.0 mm	0.62in/15.7 mm	1.02 lb