








ISSXT312 - ISSXT324
1/2" Drive Socket Flexextensions,
non-Tension, 3.02" Shank Length,
SAE



PRODUCT DETAILS

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 30 degree angle offset
- Flexextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 16 Ft. Lbs. /192 In. Lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

PRODUCT ATTRIBUTES

Product		A				B	C	D	E	
JHWISSXT312	1/2 in	3.02in/76.7 mm	Yes	6	3/8 in	1.06/26.9 mm	0.90in/22.7 mm	0.63in/16.0 mm	0.28in/7.1 mm	0.45 lb
JHWISSXT314	1/2 in	3.02in/76.7 mm	Yes	6	7/16 in	1.06/26.9 mm	0.90in/22.7 mm	0.76in/19.3 mm	0.3in/7.6 mm	0.45 lb
JHWISSXT316	1/2 in	3.02in/76.7 mm	Yes	6	1/2 in	1.06/26.9 mm	0.90in/22.7 mm	0.76in/19.3 mm	0.34in/8.6 mm	0.49 lb
JHWISSXT320	1/2 in	3.02in/76.7 mm	Yes	6	5/8 in	1.06/26.9 mm	0.90in/22.7 mm	0.90in/22.7 mm	0.44in/11.2 mm	0.45 lb
JHWISSXT324	1/2 in	3.02in/76.7 mm	Yes	6	3/4 in	1.25/31.8 mm	1.00in/25.4 mm	1.12in/28.4 mm	0.56in/14.2 mm	0.53 lb