








ISSXTM1013 - ISSXTM1018
1/2" Drive Socket Flexextensions,
non-Tension, 10.57" Shank Length,
Metric



PRODUCT DETAILS

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 30 degree angle offset
- Flexextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 16 Ft. Lbs. /192 In. Lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

PRODUCT ATTRIBUTES

Product		A				B	C	D	E	
JHWISXTM1013	1/2 in	10.57in/268.5 mm	Yes	6	13 mm	1.06/26.9 mm	0.90in/22.7 mm	0.76in/19.3 mm	0.34in/8.6 mm	0.81 lb
JHWISXTM1016	1/2 in	10.57in/268.5 mm	Yes	6	16 mm	1.06/26.9 mm	0.90in/22.7 mm	0.90in/22.7 mm	0.45in/11.4 mm	0.81 lb
JHWISXTM1018	1/2 in	10.57in/268.5 mm	Yes	6	18 mm	1.06/26.9 mm	1.00in/25.4 mm	1.00in/25.4 mm	0.45in/11.4 mm	0.84 lb