



14-1216 - 14-1240
**1/2" Deep Impact Socket, 12 Point,
SAE**



PRODUCT DETAILS

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Designed for maximum engagement on 12 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability

PRODUCT ATTRIBUTES

Product			A	B	C	D	E		F	
JHW14-1216	1/2 in	1/2 in	3-1/4 in	29/32 in	13/16 in	13/32 in	2-5/8 in	15/32 in	13/32 in	0.32 lb
JHW14-1218	1/2 in	9/16 in	3-1/4 in	29/32 in	7/8 in	13/32 in	2-5/8 in	15/32 in	13/32 in	0.34 lb
JHW14-1220	1/2 in	5/8 in	3-1/4 in	31/32 in	31/32 in	15/32 in	2-7/16 in	5/8 in	15/32 in	0.4 lb
JHW14-1222	1/2 in	11/16 in	3-1/4 in	1-1/16 in	1-1/16 in	1/2 in	2 in	5/8 in	1/2 in	0.49 lb
JHW14-1224	1/2 in	3/4 in	3-1/4 in	1-1/8 in	1-1/8 in	9/16 in	2 in	11/16 in	9/16 in	0.54 lb
JHW14-1226	1/2 in	13/16 in	3-1/4 in	1-1/4 in	1-1/4 in	5/8 in	2 in	25/32 in	5/8 in	1.43 lb
JHW14-1228	1/2 in	7/8 in	3-1/2 in	1-5/16 in	1-5/16 in	9/16 in	2-1/4 in	7/8 in	9/16 in	0.81 lb
JHW14-1230	1/2 in	15/16 in	3-1/2 in	1-3/8 in	1-3/8 in	3/4 in	2-1/4 in	15/16 in	3/4 in	0.88 lb
JHW14-1232	1/2 in	1 in	3-1/2 in	1-7/16 in	1-7/16 in	3/4 in	2-1/4 in	1 in	3/4 in	0.94 lb
JHW14-1234	1/2 in	1 1/16 in	3-1/2 in	1-9/16 in	1-9/16 in	25/32 in	2-1/4 in	1-1/32 in	25/32 in	1.14 lb
JHW14-1236	1/2 in	1 1/8 in	3-1/2 in	1-5/8 in	1-5/8 in	13/16 in	2-1/4 in	1-1/8 in	13/16 in	1.23 lb
JHW14-1238	1/2 in	1 3/16 in	3-1/2 in	1-11/16 in	1-11/16 in	13/16 in	2-1/4 in	1-3/16 in	13/16 in	1.27 lb
JHW14-1240	1/2 in	1 1/4 in	3-1/2 in	1-3/4 in	1-3/4 in	1 in	2-21/32 in	1-1/4 in	1 in	1.34 lb