

4-612 - 4-648

1/2" Drive Shallow Impact Sockets, 6 Point, Black Industrial Finish, SAE



PRODUCT DETAILS

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability

PRODUCT ATTRIBUTES

| Product | | | A | В | C | D | E | Ø | F | lb |
|----------|--------|--------------|-------------|---------------|---------------|--------------|--------------|--------------|-------------|---------|
| JHW4-612 | 1/2 in | 3/8 in | 1-1/2 in | 29/32 in | 19/32 in | 1/4 in | 7/8 in | 11/32 in | 11/16 in | 0.11 lb |
| JHW4-614 | 1/2 in | 7/16 in | 1-1/2 in | 29/32 in | 23/32 in | 5/16 in | 7/8 in | 13/32 in | 11/16 in | 0.14 lb |
| JHW4-616 | 1/2 in | 1/2 in | 1-1/2 in | 29/32 in | 13/16 in | 13/32 in | 7/8 in | 15/32 in | 11/16 in | 0.15 lb |
| JHW4-618 | 1/2 in | 9/16 in | 1-1/2 in | 29/32 in | 7/8 in | 13/32 in | 7/8 in | 15/32 in | 11/16 in | 0.17 lb |
| JHW4-620 | 1/2 in | 5/8 in | 1-1/2 in | 31/32 in | 31/32 in | 15/32 in | 7/8 in | 1/2 in | | 0.17 lb |
| JHW4-622 | 1/2 in | 11/16 in | 1-1/2 in | 1-1/16 in | 1-1/16 in | 13/16 in | 27/32 in | 5/8 in | | 0.22 lb |
| JHW4-624 | 1/2 in | 3/4 in | 1-1/2 in | 1-1/8 in | 1-1/8 in | 13/16 in | 27/32 in | 11/16 in | | 0.25 lb |
| JHW4-626 | 1/2 in | 13/16 in | 1-1/2 in | 1-1/4 in | 1-1/4 in | 13/16 in | 13/16 in | 25/32 in | | 0.33 lb |
| JHW4-628 | 1/2 in | 7/8 in | 1-1/2 in | 1-5/16 in | 1-5/16 in | 13/16 in | 13/16 in | 7/8 in | | 0.35 lb |
| JHW4-630 | 1/2 in | 15/16 in | 1-3/4 in | 1-3/8 in | 1-3/8 in | 1-1/32 in | 1-1/16 in | 15/16 in | | 0.43 lb |
| JHW4-632 | 1/2 in | 1 in | 1-3/4 in | 1-7/16 in | 1-7/16 in | 1-1/32 in | 1-1/16 in | 1 in | | 0.46 lb |
| JHW4-634 | 1/2 in | 1-1/16 in | 2 in | 1-9/16 in | 1-9/16 in | 1-1/4 in | 1-9/32 in | 1-1/32 in | | 0.66 lb |
| JHW4-636 | 1/2 in | 1-1/8 in | 2 in | 1-5/8 in | 1-5/8 in | 1-1/4 in | 1-9/32 in | 1-1/8 in | | 0.68 lb |
| JHW4-638 | 1/2 in | 1-3/16 in | 2 in | 1-11/16 in | 1-11/16 in | 1-1/4 in | 1-9/32 in | 1-5/32 in | | 0.73 lb |
| JHW4-640 | 1/2 in | 1-1/4 in | 2 in | 1-3/4 in | 1-3/4 in | 13/16 in | 1-9/32 in | 1-7/32 in | | 0.79 lb |
| JHW4-642 | 1/2 in | 1-5/16 in | 2 in | 1-1/2 in | 1-7/8 in | 7/8 in | 1-3/8 in | 1-1/16 in | | 0.78 lb |
| JHW4-644 | 1/2 in | 1-3/8 in | 2 in | 1-1/2 in | 1-15/16 in | 7/8 in | 1-3/8 in | 1-1/16 in | | 0.82 lb |
| JHW4-646 | 1/2 in | 1-7/16 in | 2 in | 1-1/2 in | 2 in | 29/32 in | 1-3/8 in | 1-1/16 in | | 0.91 lb |
| JHW4-648 | 1/2 in | 1-1/2 in | 2 in | 1-9/16 in | 2-1/8 in | 29/32 in | 1-3/8 in | 1-1/16 in | | 1.06 lb |