

4-612 - 4-648

1/2" Drive Shallow Impact Sockets, 6 Point, Black Industrial Finish, SAE



PRODUCT DETAILS

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability

PRODUCT ATTRIBUTES

Product			A	В	C	D	E	Ø	F	lb
JHW4-612	1/2 in	3/8 in	1-1/2 in	29/32 in	19/32 in	1/4 in	7/8 in	11/32 in	11/16 in	0.11 lb
JHW4-614	1/2 in	7/16 in	1-1/2 in	29/32 in	23/32 in	5/16 in	7/8 in	13/32 in	11/16 in	0.14 lb
JHW4-616	1/2 in	1/2 in	1-1/2 in	29/32 in	13/16 in	13/32 in	7/8 in	15/32 in	11/16 in	0.15 lb
JHW4-618	1/2 in	9/16 in	1-1/2 in	29/32 in	7/8 in	13/32 in	7/8 in	15/32 in	11/16 in	0.17 lb
JHW4-620	1/2 in	5/8 in	1-1/2 in	31/32 in	31/32 in	15/32 in	7/8 in	1/2 in		0.17 lb
JHW4-622	1/2 in	11/16 in	1-1/2 in	1-1/16 in	1-1/16 in	13/16 in	27/32 in	5/8 in		0.22 lb
JHW4-624	1/2 in	3/4 in	1-1/2 in	1-1/8 in	1-1/8 in	13/16 in	27/32 in	11/16 in		0.25 lb
JHW4-626	1/2 in	13/16 in	1-1/2 in	1-1/4 in	1-1/4 in	13/16 in	13/16 in	25/32 in		0.33 lb
JHW4-628	1/2 in	7/8 in	1-1/2 in	1-5/16 in	1-5/16 in	13/16 in	13/16 in	7/8 in		0.35 lb
JHW4-630	1/2 in	15/16 in	1-3/4 in	1-3/8 in	1-3/8 in	1-1/32 in	1-1/16 in	15/16 in		0.43 lb
JHW4-632	1/2 in	1 in	1-3/4 in	1-7/16 in	1-7/16 in	1-1/32 in	1-1/16 in	1 in		0.46 lb
JHW4-634	1/2 in	1-1/16 in	2 in	1-9/16 in	1-9/16 in	1-1/4 in	1-9/32 in	1-1/32 in		0.66 lb
JHW4-636	1/2 in	1-1/8 in	2 in	1-5/8 in	1-5/8 in	1-1/4 in	1-9/32 in	1-1/8 in		0.68 lb
JHW4-638	1/2 in	1-3/16 in	2 in	1-11/16 in	1-11/16 in	1-1/4 in	1-9/32 in	1-5/32 in		0.73 lb
JHW4-640	1/2 in	1-1/4 in	2 in	1-3/4 in	1-3/4 in	13/16 in	1-9/32 in	1-7/32 in		0.79 lb
JHW4-642	1/2 in	1-5/16 in	2 in	1-1/2 in	1-7/8 in	7/8 in	1-3/8 in	1-1/16 in		0.78 lb
JHW4-644	1/2 in	1-3/8 in	2 in	1-1/2 in	1-15/16 in	7/8 in	1-3/8 in	1-1/16 in		0.82 lb
JHW4-646	1/2 in	1-7/16 in	2 in	1-1/2 in	2 in	29/32 in	1-3/8 in	1-1/16 in		0.91 lb
JHW4-648	1/2 in	1-1/2 in	2 in	1-9/16 in	2-1/8 in	29/32 in	1-3/8 in	1-1/16 in		1.06 lb