



**33719 - 33760**  
**3/4" Drive Deep Sockets, 6 point,**  
**Metric**







---

## PRODUCT DETAILS

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Designed for maximum engagement on 6 point fasteners

PRODUCT ATTRIBUTES

Product			<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>		<b>F</b>	
<b>JHW33719</b>	3/4 in	19-mm	3-35/64 in	1-19/64 in	1-5/32 in	1-1/64 in	1-3/16 in	45/64 in		0.64 lb
<b>JHW33722</b>	3/4 in	22-mm	3-35/64 in	1-27/64 in	1-17/64 in	1-1/64 in	1-3/16 in	45/64 in		0.82 lb
<b>JHW33723</b>	3/4 in	23-mm	3-35/64 in	1-27/64 in	1-5/16 in	1-1/64 in	1-3/16 in	45/64 in		0.85 lb
<b>JHW33724</b>	3/4 in	24-mm	3-35/64 in	1-27/64 in	1-11/32 in	1-1/64 in	1-3/16 in	45/64 in		0.88 lb
<b>JHW33727</b>	3/4 in	27-mm	3-35/64 in	1-27/64 in	1-1/2 in	1-7/64 in	1-3/16 in	15/16 in		0.91 lb
<b>JHW33730</b>	3/4 in	30-mm	3-35/64 in	1-27/64 in	1-21/32 in	1-7/64 in	1-3/16 in	1-1/16 in		1.06 lb
<b>JHW33732</b>	3/4 in	32-mm	3-35/64 in	1-27/64 in	1-47/64 in	1-7/64 in	1-3/16 in	1-9/64 in		1.13 lb
<b>JHW33735</b>	3/4 in	35-mm	3-35/64 in	1-1/2 in	1-57/64 in	1-3/16 in	1-7/64 in	1-17/64 in		1.29 lb
<b>JHW33736</b>	3/4 in	36-mm	3-35/64 in	1-1/2 in	1-31/32 in	1-3/16 in	1-7/64 in	1-19/64 in		1.4 lb
<b>JHW33738</b>	3/4 in	38-mm	3-35/64 in	1-1/2 in	2-1/32 in	1-11/32 in	15/16 in	1-3/8 in		1.46 lb
<b>JHW33741</b>	3/4 in	41-mm	3-35/64 in	1-37/64 in	2-13/64 in	1-11/32 in	15/16 in	1-1/2 in		1.71 lb
<b>JHW33746</b>	3/4 in	46-mm	3-35/64 in	1-21/32 in	2-7/16 in	1-11/32 in	15/16 in	1-21/32 in		2 lb
<b>JHW33750</b>	3/4 in	50-mm	3-35/64 in	1-21/32 in	2-43/64 in	1-27/64 in	15/16 in	1-21/32 in		2.48 lb
<b>JHW33755</b>	3/4 in	55-mm	3-15/16 in	1-49/64 in	2-29/32 in	1-1/2 in	25/32 in	1-11/16 in		3.2 lb
<b>JHW33760</b>	3/4 in	60-mm	3-61/64 in	1-49/64 in	3-5/32 in	1-37/64 in	5/8 in	1-49/64 in		3.57 lb