



7M-627 - 7M-675





**1" Drive Shallow Impact Sockets, 6
Point, Metric**



PRODUCT DETAILS

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove
- Dual marked with corresponding SAE size

PRODUCT ATTRIBUTES

Product			A	B	C	D	E		F	
JHW7M-627	1 in	27-mm	2-1/4 in	2-1/8 in	1-3/4 in	11/16 in	1-1/16 in	3/4 in	7/8 in	1.39 lb
JHW7M-630	1 in	30-mm	2-1/4 in	2-1/8 in	1-7/8 in	11/16 in	1-1/16 in	13/16 in	7/8 in	1.36 lb
JHW7M-632	1 in	32-mm	2-3/8 in	2-1/8 in	2 in	3/4 in	1-3/16 in	15/16 in	7/8 in	1.46 lb
JHW7M-635	1 in	35-mm	2-1/2 in	2-1/8 in	2-1/8 in	7/8 in	1-5/16 in	1-3/8 in		1.46 lb
JHW7M-638	1 in	38-mm	2-5/8 in	2-1/4 in	2-11/32 in	15/16 in	1-15/32 in	1-1/2 in	1-5/8 in	1.88 lb
JHW7M-641	1 in	41-mm	2-3/4 in	2-1/4 in	2-3/8 in	1-1/16 in	1-5/8 in	1-19/32 in	1-3/4 in	1.85 lb
JHW7M-646	1 in	46-mm	2-15/16 in	2-3/8 in	2-3/4 in	1-3/16 in	1-23/32 in	1-13/16 in	1-15/16 in	2.63 lb
JHW7M-650	1 in	50-mm	3 in	2-3/8 in	2-3/4 in	1-1/4 in	1-27/32 in	1-61/64 in	2 in	2.53 lb
JHW7M-660	1 in	60-mm	3-1/2 in	2-3/8 in	3-1/2 in	1-1/2 in	2-11/32 in	1-3/4 in	2-1/2 in	4.52 lb
JHW7M-665	1 in	65-mm	3-5/8 in	2-3/8 in	3-5/8 in	1-5/8 in	2-1/8 in	2-1/4 in	2-5/8 in	4.67 lb
JHW7M-670	1 in	70-mm	3-7/8 in	2-3/8 in	3-3/4 in	1-13/16 in	2-21/32 in	2-3/4 in	2-7/8 in	4.97 lb
JHW7M-675	1 in	75-mm	4-3/16 in	2-3/8 in	4-1/8 in	2-1/32 in	2-11/16 in	2-15/16 in	3-1/8 in	6.9 lb