

## 6CD

## **Double Acting Cylinders**



## PRODUCT DETAILS

- Rod wiper seals out dirt and contamination
- High strength steel construction from gun drilled solid bar
- High flow 3/8" NPTF couplers


- One piece high grade alloy bearing for side load protection and long life
- Ideal for pushing and pulling
- Maximum working pressure: 1, psi / 7 bar













## PRODUCT ATTRIBUTES

ict: JHW6CD10T10	P	roduct: J	-IW6CD	10T12	
10 t 10.04 in	16.14 in	<u>_</u> 10	t 😓	11.97 in	Α
26.18 in <b>C</b> 1.69 in <b>D</b>	2.87 in	<b>B</b> 30 i	C	1.69 in	D
1.37 in <b>F</b> 1.38 in <b>G</b>	1.42 in	<b>E</b> 1.37	in <b>F</b>	1.38 in	G
2.09 in 2-1/4-14 in M	1.02 in	2.09	in	2-1/4-14 i	n N
0.98 in <b>X Y</b>		0.98	in X		Ÿ
11.4t 🗘	3.8 t	7	掃	11.4 t	Ĉ
2.23 in <sup>2</sup> 0.74 in <sup>2</sup>	22.41	2.2	3 0	0.74 in <sup>2</sup>	<u>-</u>
7.47 in	in <sup>3</sup>	in²		30 lb	₽
15 25.7 15	Ľ	0.0			
ict: JHW6CD30T08	P	roduct: JI	HW6CD	30T15	
30 t 5 8.15 in A	15.31	<u></u> 30		14.49 ir	
22.46	in on the	D 36.1			<u> </u>
in C 2.87 in D	3.98 in		<u> </u>	2.87 in	느
2.13 in F 1.97 in G	1.65 in	2.13		1.97 in	-
2.91 in 3-5/16-12 in V	1.93 in	2.91	÷	3-5/16-12	in \
0.98 in <b>X Y</b>		O.98	in X		1
32.9 t	16.2 t		ĮĮĮ	32.9 t	<u></u>
6.49 in <sup>2</sup> 3.19 in <sup>2</sup>	52.93 in <sup>3</sup>	6.49	<b>←</b>	3.19 in <sup>2</sup>	
26.02 lb 43 lb		← <b>■</b> 46.2	lb lb	60.6 lb	
ct: JHW6CD55T06	P	roduct: JI	HW6CD	55T13	
55 t 🖒 6.18 in 🛕 1	3.03 in	<u></u>	t 🕹	> 13.19 in	A
19.21 in <b>C</b> 3.74 in <b>D</b>	5 in	<b>B</b> 33.2	3 in <b>C</b>	3.74 in	D
3.14 in <b>F</b> 2.76 in <b>G</b>	1.14 in	<b>E</b> 3.14	in F	2.76 in	G
2.87 in <b>L</b> 5-12 in <b>V</b>	1.73 in	2.87	' in	5-12 in	M
0.98 in <b>X Y</b>		<b>K</b> 0.98	in X	{	Y
Ţ∰ 55.7 t 🗘	16.2 t	Z	ĪŦ	55.7 t	Â
10.99 in <sup>2</sup> 3.19 in <sup>2</sup> 6	7.93 in <sup>3</sup>	10.99	e in²	3.19 in <sup>2</sup>	<u> </u>
19.74 in lb 70.5 lb		← 42.1	14-2-	→ I	
_	Ľ			-	
ct: JHW6CD55T20	P	roduct: JI	HW6CD	75T06	
55 t 5 20.12 in A 2	8.86 in	<u>^</u> 75	t 50	≻ 6.1 in	1
49.98 in <b>C</b> 3.74 in <b>D</b>	5 in	<b>R</b> 19.8		4.53 ir	-/-
	2.48 in	F 3.75	=	2.76 ir	
	1.73 in	H 2.8		5-3/4-12	-
0.98 in <b>X</b>		K 1.5	-	7	1
55.71	16.2 t	7 "		81.7 t	- [
10 1	21.09	16.	09	A 5 10 in	. =
3.1911	in <sup>3</sup>	in	2		
64.24 in   1b   146.2 lb		<b>-</b> ■ 31.2	1 in Ib	93.7 lb	
et: JHW6CD75T13	Р	roduct: JI	HW6CD	100T06	
		_			Λ
22.92	0.71 in	100		6.57 in	A
33.82 C 4.53 in D	5.75 in	<b>D</b> in	C	5.12 in	ט
3.75 in <b>F</b> 2.76 in <b>G</b>	1.18 in	E 3.75		2.95 in	G
2.8 in <b>L</b> 5-3/4-12 in <b>M</b>	1.5 in	2.95 in	<u> </u>	6-7/8-12 in	V
1.5 in <b>X</b>		K 1.38	X	5.47 in	Y
81.7 t	25.9 t	<b>Z</b> 0.98	<b>‡</b>	104.4 t	Ŷ
16.09 5.12 in <sup>2</sup>	210.93 in <sup>3</sup>	20.5°		9.58 in <sup>2</sup>	ı-Þ
67.06 lb 136.8 lb		62.9i	i lb	138.6 lb	
		in			
et: JHW6CD100T13	P	roduct: JI	HW6CD	100T18	
1.1 1.1		Δ.	1. /		Λ
33.74	.63 in	100		18.15 in	A
in C 5.12 in D 6.	97 in	B 45.2	=	5.12 in	Ž
5	22 in	3.75	in F	2.95 in	G
6-7/8-12	97 in	2.95	in	6-7/8-12 in	M
2.95 In  IVI 1.					
2.95 in L in IVI 1.	10UNC in	<b>K</b> 1.38	in <b>X</b>	5.47 in	
1.38 in X 5.47 in Y 3/4"		<b>K</b> 1.38 <b>Z</b> 0.98	<b>→</b>	104.4 t	Â
1.38 in X 5.47 in Y 3/4*.  0.98 in 104.4 t 4	in	-	in III	104.4 t	₽ P