




6CH Hollow Hole Cylinders



PRODUCT DETAILS

- 6 standard models
- Ideal for some pulling and pushing applications
- Heavy duty compression spring
- Dual wipers help prevent contamination
- Collar thread protector
- High flow coupler with dust cap
- Easy-to-read window scale
- Light weight
- Automatic lock in CCW direction for removing screws
- Accuracy: $\pm 6\%$ of indicated value, CW, from 2% to 1% of full scale
- Individually serialized with matching certificate of calibration traceable to N.I.S.T
- • Meets or exceeds ASME B17.3 - 21



PRODUCT ATTRIBUTES

Product: **6CH12T03**

	12 t		3 in		2.91 in
PSI	8236 psi		8.72 in ³	D	2.76 in
G	0.75 in	H	2-3/4"-16 in	L	1.81 in
J		K		X	2 in
Y	5/16"-18UNC in	Z	0.35 in	lb	8.6 lb
A	7.24 in	B	10.24 in	C	0.77 in
E	1.38 in				

Product: **JHW6CH20T02**

	20 t		2.01 in		4.9 in
PSI	8167 psi		9.83 in ³	D	3.92 in
G	0.75 in	H	3-7/8-12 in	L	1.5 in
J	1-9/16"-16UN in	K	0.75 in	X	3.25 in
Y	3/8"-16UNC in	Z	0.37 in	lb	15.9 lb
A	6.38 in	B	8.39 in	C	1.063 in
E	2.15 in				

Product: **JHW6CH20T06**

	20 t		6.06 in		4.9 in
PSI	8167 psi		29.7 in ³	D	3.92 in
G	0.75 in	H	3-7/8-12 in	L	1.5 in
J	1-9/16"-16UN in	K	0.75 in	X	3.25 in
Y	3/8"-16UNC in	Z	0.37 in	lb	29.5 lb
A	12.05 in	B	18.11 in	C	1.063 in
E	2.15 in				

Product: **JHW6CH30T02**

	30 t		2.52 in		6.32 in
PSI	9488 psi		15.93 in ³	D	4.5 in
G	0.81 in	H	4-1/2-12 in	L	1.75 in
J	1-13/16"-16UN in	K	0.87 in	X	
Y	3/8"-16UNC in	Z	0.55 in	lb	22.9 lb
A	7.05 in	B	9.57 in	C	1.311 in
E	2.48 in				

Product: **JHW6CH30T06**

	30 t		6.11 in		6.32 in
PSI	9488 psi		38.67 in ³	D	4.5 in
G	0.81 in	H	4-1/2-12 in	L	1.75 in
J	1-13/16"-16UN in	K	0.87 in	X	
Y	3/8"-16UNC in	Z	0.55 in	lb	43 lb
A	13.02 in	B	19.13 in	C	1.311 in
E	2.48 in				

Product: **JHW6CH60T03**

	60 t		3 in		13.05 in
PSI	9195 psi		39.1 in ³	D	6.252 in
G	1 in	H	6-1/4-12 in	L	2 in
J	2-3/4"-16UN in	K	0.75 in	X	
Y	1/2"-13UNC in	Z	0.55 in	lb	
A	9.77 in	B	12.77 in	C	2.126 in
E	3.66 in				

Product: **JHW6CH100T03**

	100 t		3 in		22.13 in
PSI	9036 psi		66.31 in ³	D	8.386 in
G	1.06 in	H	6-3/8-12 in	L	2.38 in
J	4"-16UN in	K	0.98 in	X	7.01 in
Y	5/8"-11UNC in	Z	0.75 in	lb	113.3 lb
A	10 in	B	13 in	C	3.11 in
E	4.92 in				