

9029 R US-9035 R US

ERGO[™] Central Nut Wide Opening Jaw Adjustable Wrenches with Rubber Handle and Phosphate Finish



PRODUCT DETAILS

Adjustable wrenches developed according to the scientific ERGO[™] process

• Extra-wide jaw opening with a shorter handle than a standard wrench offers accessibility to work in confined spaces

- Jaw will not fall out even at maximum opening of the wrench
- Head combines slim design for accessibility with strength for performance

• Laser scale in mm for pre-adjusting and accurate measurement


• Skydrol- and oil-resistant rubber handle

• High-performance alloy steel forged in single piece

• Phosphate, precision-hardened and anticorrosion treated

- Left turning screw
- Standards: ISO 6787, DIN 3117, ASME
- B107.8-2003 and BS 6333
- Maximum comfort with minimum effort thanks to ergonomic design
- Ergonomically designed thermoplastic elastomer handle distributes pressure uniformly in the hand, reducing the risk for work related injuries
- The handle never feels too warm or too cold and tolerates oil and grease. Soft, high-friction surface reduces the risk of slipping
- Parallel jaws placed at a 15° angle provide a firm grip and best reach
- Higher capacity and accessibility with wider opening jaws and shorter handle

• Ultimate strength through precision hardening and high-performance alloy steel



PRODUCT ATTRIBUTES

| Product | Α | Α | В | С | D | Ε | g |
|-----------|--------|-------|-------|--------|---------|-------|-------|
| 9029 R US | 170 mm | 6 in | 32 mm | 5 mm | 12.8 mm | 29 mm | 220 g |
| 9031 R US | 218 mm | 8 in | 38 mm | 5 mm | 13.4 mm | 34 mm | 340 g |
| 9033 R US | 270 mm | 10 in | 46 mm | 8 mm | 17.8 mm | 41 mm | 525 g |
| 9035 R US | 324 mm | 12 in | 55 mm | 9.5 mm | 21.5 mm | 50 mm | 825 g |