



36607 - 36619

**3/8" Drive shallow Impact Sockets,  
12 Point, Metric**







---

## PRODUCT DETAILS

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Designed for maximum engagement on 6 or 12 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove

PRODUCT ATTRIBUTES

Product			<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>		<b>F</b>	
<b>JHW36607</b>	3/8 in	7-mm	1-1/8 in	3/4 in	1/2 in	3/8 in		3/8 in	1/2 in	0.08 lb
<b>JHW36608</b>	3/8 in	8-mm	1-1/8 in	3/4 in	1/2 in	3/8 in		1/2 in	1/2 in	0.08 lb
<b>JHW36609</b>	3/8 in	9-mm	1-1/8 in	3/4 in	1/2 in	3/8 in		1/2 in	1/2 in	0.08 lb
<b>JHW36610</b>	3/8 in	10-mm	1-1/8 in	3/4 in	1/2 in	3/8 in		1/2 in	1/2 in	0.08 lb
<b>JHW36611</b>	3/8 in	11-mm	1-1/8 in	3/4 in	1/2 in	1/2 in		1/2 in	1/2 in	0.08 lb
<b>JHW36612</b>	3/8 in	12-mm	1-1/8 in	3/4 in	3/4 in	1/2 in		1/2 in		0.09 lb
<b>JHW36613</b>	3/8 in	13-mm	1-1/8 in	3/4 in	3/4 in	1/2 in		1/2 in		0.08 lb
<b>JHW36614</b>	3/8 in	14-mm	1-1/8 in	3/4 in	3/4 in	1/2 in		1/2 in		0.09 lb
<b>JHW36615</b>	3/8 in	15-mm	1-1/8 in	7/8 in	7/8 in	1/2 in		1/2 in		0.11 lb
<b>JHW36616</b>	3/8 in	16-mm	1-1/8 in	7/8 in	1 in	1/2 in		1/2 in		0.15 lb
<b>JHW36617</b>	3/8 in	17-mm	1-1/8 in	7/8 in	1 in	1/2 in		5/8 in		0.13 lb
<b>JHW36618</b>	3/8 in	18-mm	1-1/8 in	1 in	1 in	1/2 in		5/8 in		0.15 lb
<b>JHW36619</b>	3/8 in	19-mm	1-1/8 in	1 in	1 in	1/2 in		5/8 in		0.15 lb