











**JHWSPR-K-14-4/JHWSPR-K-72-6  
SuperTorque™ Slotted Flat Tipped  
Screwdrivers with Rubber Grip 4 -5  
29/32 in x 0,039 - 1/4 in**



## PRODUCT DETAILS

- Screwdriver developed in accordance with the Scientific ERGO™ 11 Step Process
- Phosphate finished tip for precise accuracy
- Three-component handle for maximum user comfort, soft material with ridged undermolded material provides superior grip and greater force transmission
- Maximum comfort with minimum effort thanks to our ergonomic design
- Color-coded handle with symbol on the domed end is an easy-to-choose feature for selecting the right tip
- Flat surface on the screwdriver handle limits rolling
- Integrated handle hole allows for hanging on a peg board, securing a lanyard or inserting another screwdriver blade for added leverage
- High-performance hardened alloy steel blade with chrome plating, entirely hardened for protection against corrosion and long tool life
- Standards: ISO 2380 and DIN 5264

## PRODUCT ATTRIBUTES

| Product              |  |  |  |  |  |  |  |  |
|----------------------|---|---|---|---|--|---|---|---|
| <b>JHWSPR-K-36-4</b> |   | 3/16 in   | 4 in  |   |  |   | 7 3/4 in  | 0.14 lb   |
| <b>JHWSPR-K-72-4</b> | .039 in   | 7/32 in   | 3 15/16 in  | 0.2 in  | 1 1/8 in   | 4 13/16 in  | 8 3/4 in  | 0.15 lb   |
| <b>JHWSPR-K-72-6</b> | .039 in   | 7/32 in   | 5 29/32 in  | 0.2 in  | 1 1/8 in   | 4 13/16 in  | 10 45/64 in   | 0.16 lb   |
| <b>JHWSPR-K-14-5</b> | 3/64 in   | 1/4 in  | 4 59/64 in  | 0.24 in   | 1 3/8 in   | 4 13/16 in  | 9 23/32 in  | 0.25 lb   |
| <b>JHWSPR-K-14-6</b> | 3/64 in   | 1/4 in  | 5 29/32 in  | 0.24 in   | 1 3/8 in   | 4 13/16 in  | 10 45/64 in   | 0.26 lb   |
| <b>JHWSPR-K-56-6</b> | 3/64 in   | 5/16 in   | 5 29/32 in  | 0.28 in   | 1 3/8 in   | 4 13/16 in  | 10 45/64 in   | 0.3 lb  |
| <b>JHWSPR-K-56-7</b> | 3/64 in   | 5/16 in   | 6 57/64 in  | 0.28 in   | 1 3/8 in   | 4 13/16 in  | 11 11/16 in   | 0.31 lb   |
| <b>JHWSPR-K-38-8</b> | 1/16 in   | 3/8 in  | 7 7/8 in  | 0.31 in   | 1 3/8 in   | 6 11/32 in  | 14 7/32 in  | 0.43 lb   |